



Features & Advantages

- Elegant and compact design.
- Durable fibreglass reinforced plastic casing to withstand all weather condition.
- Small footprint for cost effective storage during off-peak season.
- Quick installation. All pipe works are pre-cut and ready for installation.
- Well resolved drainage problems through the special piping laying.

Warranty

Fittings	1 year
Filter Tank	1 year
Pump	1 year
Casing	1 year

All-in-One system for easy and fast installation for all weather. MIB filtration system provides a replacement towards concrete plant-room for swimming pool system.

Operating Limits

Model	2.5bar
Maximum water temperature	43 °C
Operating Pressure	2.5bar
Maximum Pressure	4.0bar

Optional Components

- MINDER Chlor Chlorine Generator.
- MINDER Hydro Smart Water management system.
- Control Box for Pump, Timer & Lights.
- Chlorine / Bromine Tablet Feeder.

Specification

CODE	MODEL		FILTER MODEL	PUMP MODEL	MULTIPOINT VALVE UNION SIZE		TANK Ø	FILTRATION AREA	MAX FLOW RATE		PUMP POWER	SILICA SAND
	CASE	MODEL			IMPERIAL	METRIC			m ³ /h	lpm		
71060	MIBS	MIBS550	MS21	MVP or MXB Pumps	1.5"	50mm	550	0.22	12	200	1.0HP	85
		MIBS650	MS25		1.5"	50mm	650	0.33	16	267		155
		MIBL700	MS28		1.5"	50mm	700	0.38	19	317		210
70965	MIBL	MIBL700	MS28B		2.0"	63mm	700	0.38	20	333	3.0HP	210
		MIBL800	MS32		2.0"	63mm	800	0.50	25	417	250	
		MIBL900	MS36		2.0"	63mm	900	0.64	30	500	350	

Dimensions

MODEL	A	B	C
	mm		
MIBS550	1250	1180	950
MIBS650	1250	1180	950
MIBL700	1410	1370	1070
MIBL700	1410	1370	1070
MIBL800	1410	1370	1070
MIBL900	1410	1370	1070

Pool Size Compatibility at 6 hr Turnover

MODEL	POOL SIZE	
	m ³	litre
MIBS550	72	72,000
MIBS650	96	96,000
MIBL700	114	114,000
MIBL700	120	120,000
MIBL800	150	150,000
MIBL900	180	180,000

